











PLANKS & TILES

Dimensions and Basic Data	Standard	Result
 SIZE	EN ISO 24342	PLANK: 6.5 x 1220 x 180 mm - Prime look 10 planks/box = 2,20 m ² /box 6.5 x 1524 x 180 mm - Rustic look 8 planks/box = 2,19 m ² /box 6.5 x 600 x 120 mm - Prime look, herringbone 16 planks/box = 1,15 m ² /box TILE: 6.5 x 305 x 610 mm 8 tiles/box = 1,49 m ² /box
 THICKNESS	EN ISO 24346	6.5 MM
 WEAR LAYER	EN ISO 24340	0.70 MM
LOCKING METHOD		CLIC-system
SURFACE TREATMENT		PU coating + protected with aluminium oxide (anti-scratch) and stain resistant technology.
CORE		CORE Sound reducing water resistant rigid core, SPC
Technical Data		
 BEVELLED EDGE	MICRO	4 Sides
 MASS		10.80 kg/m ²
 STANDARDS	EN 649/ EN ISO 10582	Pass
 CLASSIFICATION	EN 685 / EN ISO 10874 - Light industrial	42: Light industrial general
 CLASSIFICATION	EN 685 / EN ISO 10874 - Commercial	33: Commercial heavy
 CLASSIFICATION	EN 685 / EN ISO 10874 - Domestic	23: Domestic heavy
 REACTION TO FIRE	EN 13501-1	B _{f1} -s ¹
 STAINING RESISTANCE	EN 423	Pass
 LIGHT FASTNESS	EN ISO 105-B02	>6
 DIMENSIONAL STABILITY	EN 434 / EN ISO 23999	≤ 0.10 %

 ACOUSTIC IMPACT - NOISE REDUCTION	EN ISO 717-2/ EN ISO 140-8	ΔL _w =19DB
 ELECTRICAL BEHAVIOR - BODY VOLTAGE	EN 1815	Pass
 IDENTATION - RESIDUAL	EN 433 / EN ISO 24343-1	ss ≤ 0.1 mm
 CASTOR CHAIR - CONTINUOUS USE	EN 425 / ISO 4918	Pass
 THERMAL RESISTANCE	EN12667	<0.15 (m ² K/W)
 SLIP RESISTANCE*	BS 7976-2:2002	Plank: Dry: 62, Wet: 50
WEAR RESISTANCE	EN 660-2	T
 IMPACT RESISTANCE	EN13329	≥ 1200 mm
CLICK TENSION	Internal	200 N/5 cm
 SWELLING	ISO 24336	Pass
 FLOOR HEATING	Appropriate for all standard heating systems in cement flooring.	Not appropriate for heating films.
Dangerous substances		
 VOC EMISSION	French VOC Regulation (ISO 16000)	A+
 E1 FORMALDEHYDE - HCHO EMISSION		EN14041
REACH		Friendly reach compliant

* Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.

De in deze catalogus verstrekte informatie is met zorg samengesteld. Toch kan Rigid Floors niet instaan voor de juistheid of volledigheid van de informatie. Aan de verstrekte informatie kunnen geen rechten worden ontleend.

Les informations fournies dans ce catalogue ont été compilées avec soin. Cependant, Rigid Floors ne peut garantir l'exactitude ou l'exhaustivité des informations. Les informations fournies ne sont pas juridiquement contraignantes.

The information provided in this catalog has been compiled with care. However, Rigid Floors cannot guarantee the correctness or completeness of the information. The information provided is not legally binding.